

Innovative P2P Technology

Solutions with varying functionality?



	DISTO X3 P2P Package The P2P solution for indoor use	DISTO X4 P2P Package The P2P solution for outdoor use	DISTO S910 P2P Package The ultimate P2P solution
Scope of application	indoor	indoor and outdoor	indoor and outdoor
P2P Technology	with Leica DST 360 adapter	with Leica DST 360 adapter	integrated
Type. distance measuring accuracy	± 1.0 mm / 0.04 in	± 1.0 mm / 0.04 in	± 1.0 mm / 0.04 in
Range	0.05 up to 150 m 0.16 – 500 ft	0.05 up to 150 m 0.16 – 500 ft	0.05 up to 300 m 0.16 – 1000 ft
Range for P2P measuring Horizontal Vertical	360° - 64° up to > 90°	360° - 64° up to > 90°	360° - 40° up to 80°
Distance in m Typ. tolerance of the P2P Function	2, 5, 10 m ± 2, 5, 10 mm	2, 5, 10 m ± 2, 5, 10 mm	2, 5, 10 m ± 2, 5, 10 mm
Levelling range	± 5°	± 5°	± 5°
Memory for pictures (.jpg)			80
Memory of CAD files (.dxf) on device			20 files x 30 points
Data interface for 3D point data	Bluetooth® Smart	Bluetooth® Smart	Bluetooth® Smart WLAN
Data transfer	to DISTO Plan app to CAD software	to DISTO Plan app to CAD software	to DISTO Plan app to CAD software
Functions	P2P Distance measurements P2P Area measurements	P2P Distance measurements P2P Area measurements	P2P Distance measurements P2P Area measurements P2P Angle measurements
	BUY NOW	BUY NOW	BUY NOW